

primacare seating | product specification

Lounge and Motion Recliners Models: GC3605, GC3606, GC3608, GC3609

Recliner Dimensions (Models: GC3605, GC3606)

Overall Depth	34.5 in / 876mm
Overall Width	29.5 in / 749mm
Overall Height	45.5 in / 1156mm
Seat Depth	20 in / 508mm
Seat Width	21.5 in / 546mm
Seat Height	17 in / 432mm
Back Height - From Seat	28 in / 711mm
Armrest Clearance	22 in / 559mm
Arm Height - From Seat	7 in / 178mm
Product Weight	98 lb / 44.5 kg
Shipping Cube	22.75 ft ³ / 0.64 m ³

Motion Recliner Dimensions (Models: GC3608, GC3609)

Overall Depth	39 in / 991mm
Overall Width	30 in / 762mm
Overall Height	46.5 in / 1181mm
Seat Depth	20 in / 508mm
Seat Width	23.5 in / 597mm
Seat Height	19 in / 483mm
Back Height - From Seat	29 in / 737mm
Armrest Clearance	23.5 in / 597mm
Arm Height - From Seat	7 in / 178mm
Product Weight	110 lb / 50 kg
Shipping Cube	27.75 ft ³ / 0.79 m ³

Contact sales representative for more information.



GC3606 (recliner) with optional GC3607 headrest GC3608MRC (motion recliner w/ casters)

Upright 30" / 762mm

Full Recline 69.75" / 1772mm



TRADE SHOWROOM

Showroom 33, Level 1, 69 O'Riordan Street, Alexandria N
1300 724 174 | info@kezu.com.au

primacare seating | product specification

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

- Full Unit: 6.5 yards
- Seat/Inside Back: 1.5 yards
- Outside Back: 2.5 yards
- Arms: 2.75 yards
- Seat: 0.75 yards

Infection Control

- Side clean out on seat
- No Velcro on seat
- Seam sealing option
- Zipper sealing option
- Optional SSU armcaps are cleanable and non-porous
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

On Site Repair and Replacement

- All components are field replaceable including seat, back and armrests
- Removable covers on back, seat, leg and foot support
- The frame offers common hardware and mounting locations for the legs and casters allowing on-site conversion

Construction (Overall Frame)

- All connections are metal-to-metal. Primary seat arm connection uses patent pending die-cast zinc connectors
- Chair frame utilizes box joinery

Construction (Armcaps)

- Solid hardwood armcaps
- Armcaps are molded around a formed steel insert ensuring a metal-to-metal connection
- All armcaps are field replaceable

Construction (Seat Deck)

- Painted steel seat frame
- Heavy gauge no-sag springs
- Synthetic woven webbing under cushion

Construction (Back)

- 1 in (25mm) plywood frame construction
- Heavy gauge no-sag spring
- Synthetic woven webbing under cushion

Construction (Glides or Casters)

MODELS: GC3605, GC3606

- Non-marking nylon glides on adjustable levelers
- MODELS: GC3608, GC3609
- 4 in (102mm) diameter non-marring medical casters
 - Manual locking casters
 - Two swiveling casters on front legs. Two non-swiveling casters on rear legs

Construction (Tablet)

- Optional tablet is made of Phenolic material, an extremely dense polymer resin

Upholstery

- Seat cushion, back cushion and covers are removable/replaceable
- Front edge of seat is a seamless waterfall

Foam

- 3 in (76mm) Ultracell foam in seat and back cushions
- Meets all ASTM standards for comfort and durability

Weight Capacity

Designed for an active weight capacity of 300 lb

Warranty

Lifetime warranty on all components except the following:

- 5 year warranty on foam and textiles
- 12 year warranty on control mechanisms
- Warranty applies only to single shift, standard commercial usage (8 hours/day, 5 days/week)

Fire Rating

All textiles and foam are tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-fluoro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit [globalfurnituregroup.com](#) for additional product information including environmental certifications.



TRADE SHOWROOM

Showroom 33, Level 1, 69 O'Riordan Street, Alexandria N
1300 724 174 | info@kezu.com.au