

willow seating | product specification

Bariatric Chairs

Models: W530AUU, W530NUU, W630AUU, W630NUU

Bariatric Hip Chairs

Model: W324AUU

Dimensions

Bariatric Chairs (Models: W530_UU, W630_UU)

Overall Depth		23.5 in / 597 mm
Overall Width	W#30AUU	35.25 in / 895 mm
	W#30NUU	31.75 in / 806 mm
Overall Height		32.25 in / 819 mm
Seat Depth		17 in / 432 mm
Seat Width		29 in / 737 mm
Seat Height		18.25 in / 464 mm
Back Height - From Seat		15.25 in / 387 mm
Product Weight		27.5-34 lbs / 12.5-15.5 kg
Shipping Cube	W#30AUU	20.5 ft ³ / 0.58 m ³
	W#30NUU	16.75 ft ³ / 0.47 m ³

Bariatric Hip Chair, 24" High (Model: W324AUU)

Overall Depth	24.25 in / 616 mm
Overall Width	35.25 in / 895 mm
Overall Height	38.5 in / 978 mm
Seat Depth	17.5 in / 445 mm
Seat Width	29 in / 737 mm
Seat Height	23.25 in / 591 mm
Back Height - From Seat	15.25 in / 387 mm
Product Weight	38 lbs. / 17.3 kg
Shipping Cube	23.75 ft ³ / 0.67 m ³

Contact sales representative for more information.

Features

- Four-leg and sled base bariatric chairs
 - Chairs are available with or without arms
 - Side and back cleanout gaps
 - Single piece back with small shroud covering attachment points
 - Underseat plastic shroud
 - Standard glides are dome shaped
- MODELS: W530AUU, W530NUU
- Standard height four-leg chairs stack six high on floor or up to eight high on a dolly (Bariatric dolly: WDOL30)
- MODELS: W324AUU, W630_UU
- Hip chairs and sled base chairs do not stack

Options

- Upholstery is available any Globalcare textile (or standard Global textile, if healthcare compliance is not required)
- 17 plastic colors are available for seat shroud, back shroud and arms. Seat shroud color can be specified separately. Arms will always match the back shroud color
- Metal frame is available in 20 Sandtex paint finishes. Four plated metal finishes are also available
- Moisture barrier option (on seat only)
- Added weight options are available. Contact Customer Service for more information



W630AUU



W530NUU



W324AUU



TRADE SHOWROOM

Showroom 33, Level 1, 69 O'Riordan Street, Alexandria NSW 2015
1300 724 174 | info@kezu.com.au

willow seating | product specification

Options (continued)

MODELS: W530AUU, W630AUU, W324AUU

- Armchairs are available with two arm shapes:
 - Waterfall arms: feature a sloped front
 - Grip assist arms: feature a higher, squared-off arm which can assist users in getting into/out of seating

MODELS: W530_UU, W324AUU

- Five glide options are available on four-leg models:
 - Colored, dome shaped, nylon glides are recommended for most flooring (available in Black or Sand color)
 - White, non-marking, dome shaped, nylon glides are recommended for most flooring
 - Glides with stainless steel pads are recommended for carpet or rubber flooring
 - Glides with felt pads are recommended for vinyl, cork or laminate flooring
 - Glides with rubber pads are non-slip. They are recommended for vinyl, hardwood, laminate, stone or ceramic flooring

MODELS: W630_UU

- Floor mounting option is available for sled base models

COM Yardage

Yardage is based on unmatched materials with widths of 54 inches for seating

BARIATRIC MODELS:

- Back: 1.00 yards
- Seat: 0.75 yards
- Total: 1.75 yards

Infection Control

- No Velcro on seat. Underside of seat is covered by a plastic shroud
- Seamless seat. Seam sealing option is available for upholstered back models
- Moisture barrier option (on seat only)
- Replaceable seat and back
- For proper cleaning and disinfecting practices, the textile selection needs to be identified. It is vital that following any chemical application a clear water wipe down occur to avoid chemical build up that will lead to deterioration of the textile. Contact Global should information on using a specific disinfectant be required

Construction (Chair Frame)

- Welded steel frame
- 1 in (25 mm) diameter steel tube, 13 gauge

MODEL: W324AUU

- Hip chairs include a flat steel footrest surface, welded to the lower frame. Height from floor: 6.5 in (165 mm)

Construction (Seat and Back)

- Seat pan is 0.5 in (13 mm) thick plywood, 10-ply
- Back pan is 0.625 in (16 mm) thick plywood, 8-ply
- Metal inserts provide metal-to-metal connections with chair frame
- Plastic underseat shroud and back shroud

Construction (Arms)

MODELS: W530AUU, W630AUU, W324AUU

- Nylon arms
- Forward grip arms extend to the front edge of seat

Upholstery

- Seat and back can be upholstered in fabric, coated textiles or leather

Foam

- 1 in (25 mm) thick molded seat foam
- 0.75 in (19 mm) thick molded back foam

Weight Capacity

- Bariatric seating has an active weight capacity of 600 lbs.

Warranty

Bariatric seating is covered by heavy duty warranty:

- Warranty covers applies to 24/7 usage
- 5 year warranty on foam and textiles (a textile with durability rating of 100,000 or more double rubs must be selected)
- 12 year warranty on all other parts

Fire Rating

All foam and textiles are tested and certified, meeting California Technical Bulletin 117 (CAL TB 117-2013) standards.

Environmental

View [Environmental Data Sheets](#) online.

All foam is produced without using any ozone depleting chloro-flouro chemicals.

Awards/Certifications

- Meets or exceeds all applicable BIFMA standards for safety and durability
- Manufactured in ISO 9001 and 14001 certified facilities

Please visit globalfurnituregroup.com for additional product information including industry and environmental certifications.



TRADE SHOWROOM

Showroom 33, Level 1, 69 O'Riordan Street, Alexandria NSW 2015
1300 724 174 | info@kezu.com.au